

Item	Type	Description	Item Number
<b>LED Strips</b>	White	Length: .5 meter (18")	IL-TAPE-WHT-0.5
		Length: 1.5 meters (4.9')	IL-TAPE-WHT-1.5
		Length: 5 meters (16.4')	IL-TAPE-WHT-5.0
	Black	Length: .5 meter (18")	IL-TAPE-BLK-0.5
		Length: 1.5 meters (4.9')	IL-TAPE-BLK-1.5
		Length: 5 meters (16.4')	IL-TAPE-BLK-5.0
<b>Base and Lid</b>	1.2 meters (4')	White	IL-COVERWHT
		Tan	IL-COVERTAN
		Dark Brown	IL-COVERBRN
<b>Controller</b>	Gen I Localized Controller	Max. 520' of LED non-linkable strips	IL-CONTROL1
	Gen II App-based Control	Max 260' of LED linkable strips*	IL-CONTROL2
<b>Extender Cables</b>		Length: 3' (black)	IL-EXT3
		Length: 10' (black)	IL-EXT10
		Length: 25' (black)	IL-EXT25
		Length: 100' (black)	IL-EXT100
<b>Splitter</b>	Y-Connector	1 female/2 males connect	IL-YCONNECT
<b>End Cap</b>		Clear	IL-CLEARENDCAP

Item	Specification	Description
<b>LED Light Output</b>	Beam Angle	120°
	Lumens	42/source, 10" spacing
	LED Channels	Red/Blue/Green
	Lumen Maintenance	50,000 hrs, L70 @ 50
<b>Electrical</b>	Input Voltage	24V
	Power Consumption	.96 Watts per Meter
<b>Control</b>	Gen I Localized Control	RF Preprogrammed DMX512
	Gen II App-based Control	Ethernet (WIFI) or Blue tooth*
<b>Housing</b>	Base & Cover Dimensions (HxWxD)	2" x 48" x 1.5"
	Base & Cover - Weight	3 oz. per foot
	Base & Cover - Material	Base - UV Treated PVC Cover - Modified Acrylic
<b>Physical</b>	Fixture Connections (LED Strips)	Integrated watertight 4-pin connectors
	Temperature Ranges	-40°F to 122°F
	Waterproofing	IP65 (not submersible in water)
	Maximum Fixtures per Data/Power Supply	520' with localized control 260' with web-based control
	UV Protection	10 year Warranty